

GG-J

H05RR-F/RN-F

ELEKTROMETAL GG-J/H05RR-F/RN-F



Primena: Za povezivanje električnih aparata (usisivača, kuhinjskih aparata, lemilica itd.) kod niskog mehaničkog stresa u domaćinstvima, kuhinjama, kancelarijama. Nije za trajnu upotrebu na otvorenom.

Application: For connection of electrical appliances (vacuum cleaners, kitchen appliances, soldering iron etc.) with low mechanical stress in households, kitchens, offices. Not for permanent outdoor use.

Materijal provodnika:	bakar	
Konstrukcija provodnika:	klasa 5	
Izolacija:	guma (EPR) EI4	
Materijal plašta:	guma (CR) EM2	
Otpornost na plamen:	VDE 0482-332-1-2/IEC 60332-1	
Maksimalna temperatura u provodniku:	60 °C	
Maksimalna temperatura tokom rada:	-25 - 60 °C	
Tip kabla:	GG-J	GG-J
Nominalni naponski nivo U _o :	300 V	300 V
Nominalni naponski nivo U:	500 V	500 V
Obeležavanje žila:	boje po VDE 0293 (HD308)	boje po VDE 0293 (HD308)
















Conductor material:	bare copper	
Conductor construction:	fine stranded, class 5	
Insulation:	rubber (EPR) EI4	
Sheathing material:	rubber (CR) EM2	
Flame retardant:	VDE 0482-332-1-2/IEC 60332-1	
Maximum temperature at conductor:	60 °C	
Max. operating temperature, fixed:	-25 - 60 °C	
Cable type:	H05RR-F	H05RN-F
Nominal voltage U _o :	300 V	300 V
Nominal voltage U:	500 V	500 V
Core identification:	colours acc. VDE 0293 (HD308)	colours acc. VDE 0293 (HD308)

GG-J/ H05RR-F

Naziv kabla	Presek	Boja	Da	CU	T	Naziv kabla	Presek	Boja	Da	CU	T
Cable name	Cross section	Color	mm	kg/km	kg/km	Cable name	Cross section	Color	mm	kg/km	kg/km
H05RR-F	02X0,75	crna / black	6,2	60	14,4	H05RR-F	04G0,75	crna / black	7,2	90	29
H05RR-F	02X1	crna / black	6,8	70	19	H05RR-F	04G1	crna / black	7,8	110	38
H05RR-F	02X1,5	crna / black	8,2	100	29	H05RR-F	04G1,5	crna / black	9,8	170	58
H05RR-F	02X2,5	crna / black	9,7	150	48	H05RR-F	04G2,5	crna / black	11,2	230	96
H05RR-F	03G0,75	crna / black	6,6	80	21,6	H05RR-F	05G0,75	crna / black	9,9	113	36
H05RR-F	03G1	crna / black	7,2	90	29	H05RR-F	05G1,5	crna / black	10,7	190	72
H05RR-F	03G1,5	crna / black	8,8	130	43	H05RR-F	05G2,5	crna / black	12,5	280	120
H05RR-F	03G2,5	crna / black	10,2	180	72						

GG-J/ H05RN-F											
Naziv kabla	Presek	Boja	Da	CU	T	Naziv kabla	Presek	Boja	Da	CU	T
Cable name	Cross section	Color	mm	kg/km	kg/km	Cable name	Cross section	Color	mm	kg/km	kg/km
H05RN-F	02X0,75	crna / black	6,2	60	14,4	H05RN-F	03G1	crna / black	7,2	90	29
H05RN-F	02X1	crna / black	6,8	70	19	H05RN-F	04X0,75	crna / black	8,8	76	29
H05RN-F	03G0,75	crna / black	6,6	80	21,6	H05RN-F	04G0,75	crna / black	8,8	76	29

Objašnjenje oznaka	Labels explanation
Da Spoljni dijаметar	Da Outer diameter
Cu Težina bakra u kablju	Cu Copper weight
T Ukupna težina kabla	T Total weight

Identifikacija žila	GG-J H05RR-F/ RN-F				
Core identification					
žile	Boje				
cores	Colors				
1	 žz/yg				
2	 pl/bl	 br/bw			
3	 žz/yg	 pl/bl	 br/bw		
4	 žz/yg	 br/bw	 cr/bc	 si/gr	
5	 žz/yg	 pl/bl	 br/bw	 cr/bc	 si/gr

Objašnjenje boja	Color explanation
žz žuto-zelena	yg yellow-green
cr crna	bc black
pl plava	bl blue
br braon	bw brown
si siva	gr gray