


J-2Y(St)H St III Bd



Primena: Bezhalogeni i vatrootporni ISDN-sistemski kabl, za povezivanje telekomunikacionih i IT komponenti do brzina od 16 Mbit/s (kat. 3). Za ugradnju u zatvorenom prostoru, iznad i ispod malterisanih površina u suvim kao i vlažnim prostorijama.

Application: Halogen free and flame retardant ISDN-System cable, for connection of telecommunication and IT components up to 16 Mbit/s (cat. 3). For installations indoor, in and under plaster, in dry as well as wet rooms.

| | |
|------------------------------------|--------------------------------|
| Materijal provodnika: | bakar |
| Izolacija: | polietilen |
| Raspored žila: | grupisane četverostruke zvezde |
| Ekran: | folija |
| Odvodna žica: | da |
| Materijal plašta: | bezhalogeno-jedinjenje HM2 |
| Otpornost na plamen: | VDE 0482-332-1-2/IEC 60332-1 |
| Gustina dima: | DIN EN 61034/IEC 61034 |
| Maksimalna temperatura tokom rada: | -5 - +50 °C |
| Otpor izolacije: | 5000 MOhm \times km |
| Otpor prenosa: | 200 Ohm/km |
| Radni kapacitet: | 45 nF/km |
| Nominalni naponski nivo U: | 225 V |
| Obeležavanje žila: | boje + prstenovi |

| | |
|------------------------------------|------------------------------|
| Conductor material: | bare copper |
| Insulation: | polyethylene |
| Stranding: | bunched star-quads |
| Screen: | foil |
| Drain wire: | yes |
| Sheathing material: | FRNC-compound HM2 |
| Flame retardant: | VDE 0482-332-1-2/IEC 60332-1 |
| Smoke density: | DIN EN 61034/IEC 61034 |
| Max. operating temperature, fixed: | -5 - +50 °C |
| Insulation resistance: | 5000 MOhm \times km |
| Transfer impedance: | 200 Ohm/km |
| Operating capacity: | 45 nF/km |
| Nominal voltage U: | 225 V |
| Core identification: | colours + rings |

Dodatni podaci: Preslušavanje: > 30 dB (@ 5-10 MHz)
Slabljenje : < 6,5 dB/100 m (@ 10 MHz)

Additional information: Cross-talk: > 30 dB (@ 5-10 MHz)
Attenuation: < 6,5 dB/100 m (@ 10 MHz)

J-2Y(St)H St III Bd

| Naziv kabla | Presek | Boja | Da | T | CU |
|-------------|---------------|-------------|------|-------|-------|
| Cable name | Cross section | Color | mm | kg/km | kg/km |
| J-2Y(St)H | 02X2X0,6 | siva / gray | 4,9 | 13 | 42 |
| J-2Y(St)H | 04X2X0,6 | siva / gray | 6,9 | 25 | 60 |
| J-2Y(St)H | 06X2X0,6 | siva / gray | 7 | 35 | 85 |
| J-2Y(St)H | 10X2X0,6 | siva / gray | 9,2 | 58 | 115 |
| J-2Y(St)H | 20X2X0,6 | siva / gray | 12 | 116 | 217 |
| J-2Y(St)H | 30X2X0,6 | siva / gray | 14,5 | 172 | 300 |

| Naziv kabla | Presek | Boja | Da | T | CU |
|-------------|---------------|-------------|------|-------|-------|
| Cable name | Cross section | Color | mm | kg/km | kg/km |
| J-2Y(St)H | 40X2X0,6 | siva / gray | 16,2 | 229 | 370 |
| J-2Y(St)H | 50X2X0,6 | siva / gray | 18,2 | 286 | 434 |
| J-2Y(St)H | 60X2X0,6 | siva / gray | 19,6 | 342 | 526 |
| J-2Y(St)H | 80X2X0,6 | siva / gray | 22,1 | 455 | 680 |
| J-2Y(St)H | 100X2X0,6 | siva / gray | 24,7 | 568 | 861 |

Objašnjenje oznaka

Da Spoljni dijametar
T Ukupna težina kabla
Cu Težina bakra u kablu

Labels explanation

Da Outer diameter
T Total weight
Cu Copper weight